

Downlight

Glyde 30w



Product Reference

Environment	Indoor
Installation	Ceiling recess /grid ceiling-600mm

Construction and Materials

Housing	Mild Steel
Lens or Diffuser	Premium High Transmission PMMA,78%
Reflector	-
Finish	Powder Coated White

Thermal Management

Heat Sink material	Aluminium
Cooling technique	Passive

Optical system

Beam Angles	General illumination-wide
Beam Direction	Fixed
Tilt	No
Swivel	No

Light technology

Led fitted	Samsung
Lumen Output at source	2973 2973 3197 3197
Co-related Color temp.	2700K 3000K 4000K 6000K
Led life time @ L70	35,000 hours
Colour rendering	>80

Electrical System


Driven with	Constant current driver
Input Voltage	100V-240V
Input Power	29.5w
Power Factor	>0.92
ATHD	<10%
Control Gear mounting	Remote

Dimming

Optional- Consult Abby Representative

Installation

For grid ceiling 600mm
 Min void in ceiling height 80mm
 Installation by Lay-in / Spring clips



Application Legend



Ordering Information

Glyde 30w

Product code

Glyde 30w, Warm white 3000K, General illumination-wide, White, Non dimmable

Glyde 30w/WW30K/ /

LED colour

Warm white 2700K
 Warm white 3000K
 Neutral white 4000K
 Cool white 6000K

WW27K
 WW30K
 NW40K
 CW60K

Beam Angle

General illumination-wide

Finish

White

Dimming option

Non dimmable
 1-10v dimmable driver 1-10
 Phase dimmable driver PHA
 Dali dimmable driver DAL

Photometry

