



ABBY
LIGHTING

SPOT & ACCENT - RECESS : **BLING F 5W**

TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment	Indoor
Installation	Ceiling Recess

CONSTRUCTION & MATERIALS

Housing	Aluminium
Lens or Diffuser	PMMA
Reflector	PC Metallised
Finish	Powder Painted White / Black

THERMAL MANAGEMENT

Heat Sink Material	Aluminium, Black Anodised
Cooling Technique	Passive

OPTICAL SYSTEM

Beam Angles (FWHM)°	Medium (36)
Beam Direction	Fixed
Tilt	No
Swivel	No

ELECTRICAL SYSTEM

Driven With	Constant Current Driver
Input Voltage	220V-240V
Input Power	4.43w
Power Factor	>0.6
ATHD	-
Control Gear Mounting	Remote

DIMMING

Dimming Options Consult ABBY Representative

LED TECHNOLOGY

Led Fitted	CREE
Lumen Output System (Delivered)*	334 358 386
Efficacy (System - lm/watt)*	75 81 87
Co-related Colour Temp.	3000K 4000K 6000K
Led Life Time @ L70 / B10	50,000 hours
Colour Rendering CRI	>80



ORDERING INFORMATION

While ordering mention **one code from each** of the following columns

PRODUCT CODE	LED COLOUR	BEAM ANGLE	FINISH	DIMMING OPTION
BLING F 5W	Warm White 3000K NW30K	Medium (36) MD	White SWH	Non Dimmable
	Neutral White 4000K NW40K		Black SBL	1-10v Dimmable Driver A Dim
	Cool White 6000K CW60K			Phase Dimmable Driver PC Dim
				Dali Dimmable Driver D Dim


BLING F 5W - CW60K - MD - SWH -

This is the ordering code for a BLING F 5W in Cool White, Medium Beam, White Finish, and Non Dimmable Driver.

INSTALLATION

Cutout in mm	37 mm
Min void in ceiling height	75 mm
Installation by	Spring clips

LINE DRAWING



Ø : 45mm x Ht : 65mm

PHOTOMETRY



APPLICATION LEGEND



Abby tries to ensure all data and information is correct at the time of publication.
Data provided is for information purposes only.
*Output data figures stated are typical values for medium beam.

www.abbylighting.com