



ABBY
LIGHTING

SPOT & ACCENT - TRIMLESS : **BETA TRIMLESS 1-WAY 8W**

TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment Indoor
Installation Ceiling Recess

CONSTRUCTION & MATERIALS

Housing Aluminium & Steel
Lens or Diffuser Clear PMMA
Reflector PC Metallised
Finish Powder Painted White / Black

THERMAL MANAGEMENT

Heat Sink Material Aluminium, Black Anodised
Cooling Technique Passive

OPTICAL SYSTEM

Beam Angles (FWHM)° Medium (36)
Beam Direction Adjustable
Tilt Yes
Swivel No

ELECTRICAL SYSTEM

Driven With Constant Current Driver
Input Voltage 220V-240V
Input Power 8.55W
Power Factor >0.8
ATHD -
Control Gear Mounting Remote

DIMMING

Dimming Options Consult ABBY Representative

LED TECHNOLOGY

Led Fitted CREE
Lumen Output System (Delivered)* 566 608 656
Efficacy (System - lm/watt)* 66 71 76
Co-related Colour Temp. 3000K 4000K 6000K
Led Life Time @ L70 / B10 50,000 hours
Colour Rendering CRI >80



ORDERING INFORMATION

While ordering mention **one code from each** of the following columns

PRODUCT CODE	LED COLOUR	BEAM ANGLE	FINISH	DIMMING OPTION
BETA TRIMLESS 1-WAY 8W	Warm White 3000K Neutral White 4000K Cool White 6000K	Medium (36)	White Black	Non Dimmable 1-10v Dimmable Driver Phase Dimmable Driver Dali Dimmable Driver
	WW30K NW40K CW60K	MD	SWH SBL	A Dim PC Dim D Dim


BETA TRIMLESS 1-WAY 8W - CW60K - MD - SWH - D Dim

This is the ordering code for a BETA TRIMLESS 1-WAY 8W in Cool White, Medium Beam, White Finish, and Dali Dimmable Driver.

INSTALLATION

Cutout in mm 76mm x 76mm
Min void in ceiling height 100 mm
Installation by Trimless Frame

LINE DRAWING



PHOTOMETRY



L: 76mm x B: 76mm x Ht : 90mm

APPLICATION LEGEND



Abby tries to ensure all data and information is correct at the time of publication. Data provided is for information purposes only. *Output data figures stated are typical values for medium beam.