



ABBY
LIGHTING

PROFILE - RECESS : **CANALAZZO R 240 60W**

TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment Indoor
Installation Ceiling Recess / Pendant^

CONSTRUCTION & MATERIALS

Housing Aluminium
Lens or Diffuser Premium High Transmission PMMA
Reflector Aluminium Matt
Finish Powder Painted White

THERMAL MANAGEMENT

Heat Sink Material Aluminium
Cooling Technique Passive

OPTICAL SYSTEM

Beam Angles (FWHM)° General Illumination
Beam Direction Fixed
Tilt No
Swivel No

ELECTRICAL SYSTEM

Driven With Constant Current Driver
Input Voltage 220V-240V
Input Power 58.44w
Power Factor >0.9
ATHD <10%
Control Gear Mounting Integral



DIMMING

Dimming Options Consult ABBY Representative

LED TECHNOLOGY

Led Fitted SAMSUNG
Lumen Output System (Delivered)* 5832 6048 6256
Efficacy (System - lm/watt)* 97 101 104
Co-related Colour Temp. 3000K 4000K 6000K
Led Life Time @ L70 / B10 50,000 hours
Colour Rendering CRI >80

ORDERING INFORMATION

While ordering mention **one code from each** of the following columns


PRODUCT CODE	LED COLOUR	BEAM ANGLE	FINISH	DIMMING OPTION
CANALAZZO R 240 60W	Warm White 3000K Neutral White 4000K Cool White 6000K	General Illumination	White	Non Dimmable 1-10v Dimmable Driver Phase Dimmable Driver Dali Dimmable Driver

CANALAZZO R 240 60W - CW60K - - SWH - D Dim

This is the ordering code for a CANALAZZO R 240 60W in Cool White, General Illumination, White Finish, and Dali Dimmable Driver.


INSTALLATION

Cutout in mm 2368 mm x 66mm
Min void in ceiling height 105 mm
Installation by Bracket Provided



LINE DRAWING

PHOTOMETRY



^Order Canalazzo Pendant as Canalazzo P & Canalazzo Recess as Canalazzo R. Please consult an Abby representative for Continuous Mounting arrangement. Abby tries to ensure all data and information is correct at the time of publication. Data provided is for information purposes only. *Output data figures stated are typical values for downlight only.