



TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment Indoor
Installation Ceiling Pendant

CONSTRUCTION & MATERIALS

Housing Aluminium
Lens or Diffuser Premium High Transmission PMMA
Reflector White Optics
Finish Powder Painted White / Black / Custom

THERMAL MANAGEMENT

Heat Sink Material Aluminium
Cooling Technique Passive

OPTICAL SYSTEM

Beam Angles (FWHM)^o General Illumination
Beam Direction Fixed
Tilt No
Swivel No

ELECTRICAL SYSTEM

Driven With Constant Current Driver
Input Voltage 220V-240V
Input Power 21.08w
Power Factor >0.9
ATHD <10%
Control Gear Mounting Remote



DIMMING

Dimming Options Consult ABBY Representative

LED TECHNOLOGY

Led Fitted	SAMSUNG		
Lumen Output System (Delivered)*	1104	1149	1182
Efficacy (System - lm/watt)*	52	54	56
Co-related Colour Temp.	3000K	4000K	6000K
Led Life Time @ L70 / B10	50,000 hours		
Colour Rendering CRI	>80		

ORDERING INFORMATION

While ordering mention **one code from each** of the following columns

PRODUCT CODE	LED COLOUR	BEAM ANGLE	FINISH	DIMMING OPTION
COCO 35 22W	Warm White 3000K Neutral White 4000K Cool White 6000K	General Illumination	White Black Custom	Non Dimmable 1-10v Dimmable Driver Phase Dimmable Driver Dali Dimmable Driver


COCO 35 22W - CW60K - - SWH - D Dim

This is the ordering code for a COCO 35 22W in Cool White, General Illumination Wide, White Finish, and Dali Dimmable Driver.


INSTALLATION

Ceiling Bracket Provided

LINE DRAWING



PHOTOMETRY



APPLICATION LEGEND



Abby tries to ensure all data and information is correct at the time of publication. Data provided is for information purposes only. *Output data figures stated are typical values.