



ABBY
LIGHTING

STUDIO ABBY - PENDANT : **DOMUS MP 30w**

TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment Indoor
Installation Ceiling Pendant

CONSTRUCTION & MATERIALS

Housing Aluminium
Lens or Diffuser Micro Prism PMMA
Reflector -
Finish Powder Painted White / Black / Custom

THERMAL MANAGEMENT

Heat Sink Material Aluminium
Cooling Technique Passive

OPTICAL SYSTEM

Beam Angles (FWHM)^o General Illumination - Wide
Beam Direction Fixed
Tilt No
Swivel No

ELECTRICAL SYSTEM

Driven With Constant Current Driver
Input Voltage 220V-240V
Input Power 29.04w
Power Factor >0.9
ATHD <10%
Control Gear Mounting Integral



DIMMING

Dimming Options Consult ABBY Representative

LED TECHNOLOGY

Led Fitted SAMSUNG
Lumen Output System (Delivered)* 2950 3118 3221
Efficacy (System - lm/watt)* 102 107 111
Co-related Colour Temp. 3000K 4000K 6000K
Led Life Time @ L70 / B10 50,000 hours
Colour Rendering CRI >80

ORDERING INFORMATION

While ordering mention **one code from each** of the following columns

PRODUCT CODE	LED COLOUR	BEAM ANGLE	FINISH	DIMMING OPTION
DOMUS MP 30W	Warm White 3000K WW30K	General Illumination - Wide	White SWH	Non Dimmable
	Neutral White 4000K NW40K		Black SBL	1-10v Dimmable Driver A Dim
	Cool White 6000K CW60K		Custom COS	Phase Dimmable Driver PC Dim
				Dali Dimmable Driver D Dim


DOMUS MP 30W - CW60K - - SBL - D Dim

This is the ordering code for a DOMUS MP 30W in Cool White, General Illumination Wide, White Finish, and Dali Dimmable Driver.

INSTALLATION

Suspension Cable (Provided)

LINE DRAWING



Ø : 550mm x Ht : 250mm

PHOTOMETRY



APPLICATION LEGEND



Abby tries to ensure all data and information is correct at the time of publication. Data provided is for information purposes only. *Output data figures stated are typical values for plain opal diffuser.