TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

Environment

Installation Ceiling Pendant / Surface^ / Recess^

CONSTRUCTION & MATERIALS

Housing Aluminium Profile & Sheet

Lens or Diffuser Premium High Transmission Poly Carbonate

Reflector White Optics

Finish Powder Painted White / Black / Custom

THERMAL MANAGEMENT

Heat Sink Material Aluminium **Cooling Technique** Passive

OPTICAL SYSTEM

Beam Angles (FWHM)° General Illumination Wide

Beam Direction Fixed Tilt No Swivel No

Dimming Options

DIMMING

Consult ABBY Representative

ELECTRICAL SYSTEM

Driven With Constant Current Driver

Input Voltage 220V-240V Input Power 24.63w **Power Factor** >0.9 **ATHD** <10%

Control Gear Mounting Integral

LED TECHNOLOGY

Led Fitted Lumen Output System (Delivered)*

Efficacy (System - Im/watt)*

Co-related Colour Temp.

Led Life Time @ L70 / B10

Colour Rendering CRI

SAMSUNG

2795 2890 2990

117

3000K 4000K 6000K 50,000 hours

STUDIO ABBY - PENDANT: CIRCULO P 45 25W

ORDERING INFORMATION

While ordering mention one code from each of the following columns



LED COLOUR

Warm White 3000K

Neutral White 4000K NW40K

WW30K

CW60K

Cool White 6000K

BEAM ANGLE General Illumination Wide

SI FINISH

SWH

Black

Custom

SBL

Non Dimmable

1-10v Dimmable Driver

DIMMING OPTION

Phase Dimmable Driver

Dali Dimmable Driver

D Dim

A Dim

PC Dim




This is the ordering code for a CIRCULO P 45 25W in Cool White, General Illumination Wide, White Finish, and Dali Dimmable Driver.


INSTALLATION

Suspension Cable (Provided)

LINE DRAWING

75mm





PHOTOMETRY

APPLICATION LEGEND













