

SPOT & ACCENTS

iKapp 24w



Product Reference

Environment	Indoor
Installation	Ceiling recess
Construction and Materials	
Housing	Aluminium and Steel
Lens or Diffuser	Clear PMMA
Reflector	PC metallised
Finish	Powder painted white/black

Thermal Management

Heat Sink material	Aluminium, Black anodised
Cooling technique	Passive

Optical System

Beam Angles (FWHM°)	Spot(16), Medium(28)
Beam Direction	Adjustable
Tilt	Yes
Swivel	No

Light Technology

Led fitted	CREE
Lumen Output at source	1773 1897
Co-related Colour temp.	3000K 4000K
Led life time @ L70	50,000 hours
Colour rendering	>80

Electrical System


Driven with	Constant current driver
Input Voltage	100V-240V
Input Power	24w
Power Factor	>0.92
ATHD	-
Control Gear mounting	Remote

Dimming

Optional- Consult Abby Representative

Installation

Cutout in mm
Min void in ceiling height
Installation by



Application Legend



Ordering Information

iKapp 24w

Product Code

iKapp 24w,
Warm white 3000K,
Medium (28), White, 1-10v
dimnable driver

iKapp24w/WW30K/MD/SWH/1-10

LED Colour

Warm white 2700K
Warm white 3000K
Neutral white 4000K

WW27K
WW30K
NW40K

Beam Angle

Spot (16)
Medium (28)

SS
MD

Finish

White
Black

SWH
SBL

Dimming Option

Non dimmable
1-10v dimmable driver
Phase dimmable driver
Dali dimmable driver

1-10
PHA
DAL

Photometry

