

Spotboy Pro SR 50 2Way | 2X10W

Product Reference

Environment Indoor

Installation Semi Recess

Construction & Materials

Housing Die Cast Aluminium,Milled Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 2x9.0W

System Power Watts 2x10.3W


Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95





Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Spotboy Pro SR 50 2Way	2X10W	WW27K	CRI80	23°(ss)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 33V-36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Spotboy Pro SR 50 2Way	2X10W	2x948	92	2700K	WW27K	CRI80	23°(SS)	White	SWH	Non Dimmable	On/Off
		2x979	95	3000K	WW30K	CRI90	30°(MD)	Black	SBL	Phase Dimmable	PDIM
		2x1030	100	4000K	NW40K		33°(WD)	Custom	CSM	Dali Dimmable	DDIM
		2x1051	102	5700K	CW57K		50°(VWD)			Bluetooth Dimmable	BTTM
		2700K-5700K		TW						Casambi	CBTM
		Warm to Dim		W2D							
Spotboy Pro SR 50 2Way	2X10W			WW27K		CRI80	23°(SS)	SWH		On/Off	