
ABBY LIGHTING

220V 240V 50/60Hz | IP20 | L80B10 >50,000h | MacAdam Step 3 | CRI 90

Optional: Dimmable | Tunable White | Uplight

Nexus 150 SDS P MPD 180 | 88W





Note : S- Soft , D- Dark

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector PC Black Cover

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral


LED Power Watts 75.6W

System Power Watts 86.9W

Operating Voltage Vin 220V- 240V/50-60Hz

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/1500mA(S) + 700mA(D)

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nexus 150 SDS P MPD 180	**88W**	**WW27K**	**CRI90**	**104°(S)+53°(D)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Nexus 150 SDS P MPD 180	**88W**	7415	85	2700K	**WW27K**	**CRI90**	104°(S)+53°(D)	White	**SWH**	Non Dimmable	**On/Off**
		7649	88	3000K	**WW30K**			Black	**SBL**	Dali Dimmable	**DDIM**
		8057	93	4000K	**NW40K**			Custom	**CSM**	Casambi	**CBTM**
		8231	95	5700K	**CW57K**						
				2700K-5700K	**TW**						
Nexus 150 SDS P MPD 180	**88W**			**WW27K**		**CRI90**	**104°(S)+53°(D)**	**SWH**		**On/Off**	