

## iNline R 120 | 20W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Integral

LED Power Watts 17.0W


System Power Watts 19.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-38Vdc/500mA

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                | Watt       | CCT          | CRI          | Angle       | Finish     | Control       |
|---------------|---------------------|------------|--------------|--------------|-------------|------------|---------------|
|               | <b>iNline R 120</b> | <b>20W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>103°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                | WATT       | LUMEN | EFFICACY | CCT          |              | CRI          | ANGLE       | FINISH     |            | CONTROL       |               |
|---------------------|------------|-------|----------|--------------|--------------|--------------|-------------|------------|------------|---------------|---------------|
| <b>iNline R 120</b> | <b>20W</b> | 2204  |          | 2700K        | <b>WW27K</b> | <b>CRI80</b> | 103°        | White      | <b>SWH</b> | Non Dimmable  | <b>On/Off</b> |
|                     |            | 2262  |          | 3000K        | <b>WW30K</b> | CRI90        |             | Black      | <b>SBL</b> | Dali Dimmable | <b>DDIM</b>   |
|                     |            | 2399  |          | 4000K        | <b>NW40K</b> |              |             | Custom     | <b>CSM</b> | Casambi       | <b>CBTM</b>   |
|                     |            | 2496  |          | 5700K        | <b>CW57K</b> |              |             |            |            |               |               |
|                     |            |       |          | 2700K-5700K  | <b>TW</b>    |              |             |            |            |               |               |
| <b>iNline R 120</b> | <b>20W</b> |       |          | <b>WW27K</b> |              | <b>CRI80</b> | <b>103°</b> | <b>SWH</b> |            | <b>On/Off</b> |               |