

## Dot F | 3W

### Product Reference

Environment Indoor  
 Installation Ceiling Recess

### Construction & Materials

Housing Milled Aluminium  
 Primary Lens PMMA  
 Primary Reflector PC metallised  
 Secondary Reflector -  
 Body Finish White,Black,Custom  
 Diffuser -  
 Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium  
 Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed  
 Tilt No  
 Swivel No

### Electrical System


Driven with Constant Current Driver  
 Input Voltage/Hz 220V- 240V/50-60Hz  
 Control Gear Included  
 Mounting Remote  
 LED Power Watts 2.2W  
 System Power Watts 2.9W  
 Operating Voltage  $V_{in}$  220-240 Vac  
 Power Factor p.f. > 0.5

### Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Dot F</b>	<b>3W</b>	<b>WW27K</b>	<b>CRI90</b>	<b>16°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Dot F</b>	<b>3W</b>	189	65	2700K <b>WW27K</b>	<b>CRI90</b>	16°(SS) <b>25°(MD)</b>	White <b>SWH</b>	Non Dimmable <b>On/Off</b>
		197	68	3000K <b>WW30K</b>		25°(MD)	Black <b>SBL</b>	Phase Dimmable <b>PDIM</b>
		212	73	4000K <b>NW40K</b>		45°(WD)	Custom <b>CSM</b>	Dali Dimmable <b>DDIM</b>
		220	76	5700K <b>CW57K</b>				
<b>Dot F</b>	<b>3W</b>			<b>WW27K</b>	<b>CRI90</b>	<b>16°(SS)</b>	<b>SWH</b>	<b>On/Off</b>



### Light Distribution



### LED Technology

Binning 3 Step MacAdam  
 LED Life Time @ L80/B10 >50000 hours  
 Colour Rendering (CRI) CRI90  
 Led Type SMD high power  
 LED Fitted -

### Controls

Standard Switchable On/Off  
 Optional PDIM,DDIM,Non Dimmable