

Xcent Pro | 20W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 17.1W





System Power Watts 19.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTMM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Xcent Pro	20W	WW27K	CRI80	24°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Xcent Pro	20W	1803	92	2700K	WW27K	CRI80	24°(SS)	White	SWH	Non Dimmable	On/Off
		1862	95	3000K	WW30K	CRI90	32°(MD)	Black	SBL	Phase Dimmable	PDIM
		1960	100	4000K	NW40K		35°(WD)	Custom	CSM	Dali Dimmable	DDIM
		1999	102	5700K	CW57K		44°(VWD)			Bluetooth Dimmable	BTMM
				2700K-5700K Warm to Dim	TW W2D					Casambi	CBTM
Xcent Pro	20W			WW27K		CRI80	24°(SS)	SWH		On/Off	