
ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3

Optional: Bluetooth | Dimmable | CRI 90

iPlane Round Recess | 10W





Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector White Optics

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote


LED Power Watts 8.8W

System Power Watts 10.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 9V-12Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	iPlane Round Recess	**10W**	**WW27K**	**CRI80**	**116°**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
iPlane Round Recess	**10W**	859	85	2700K	**WW27K**	**CRI80**	116°	White	**SWH**	Non Dimmable	**On/Off**
		889	88	3000K	**WW30K**	CRI90		Black	**SBL**	Phase Dimmable	**PDIM**
		939	93	4000K	**NW40K**			Custom	**CSM**	Dali Dimmable	**DDIM**
		970	96	5700K	**CW57K**					Bluetooth Dimmable	**BTTM**
										Casambi	**CBTM**
iPlane Round Recess	**10W**			**WW27K**		**CRI80**	**116°**	**SWH**		**On/Off**	