

Husky 100 | 15W

Product Reference

Environment Outdoor

Installation Floor Surface

Construction & Materials

Housing Die Cast Aluminium, Extruded Aluminium

Primary Lens -

Primary Reflector Aluminium White Painted

Secondary Reflector -

Body Finish Black, Grey

Diffuser Clear PC

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 12.5W


System Power Watts 14.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted -

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Husky 100	15W	WW27K	CRI80	140°	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Husky 100	15W	1339	93	2700K	WW27K	CRI80	140°	Black	SBL	Non Dimmable	On/Off
		1382	96	3000K	WW30K	CRI90		Grey	GGT	Phase Dimmable	PDIM
		1469	102	4000K	NW40K					Dali Dimmable	DDIM
		1512	105	5700K	CW57K					Bluetooth Dimmable	BTTM

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
								Casambi CBTM
Husky 100	15W			WW27K	CRI80	140°	SBL	On/Off