

Wally | 10W

Product Reference

Environment Outdoor

Installation Wall Surface,Wall Surface

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Grey

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 9.0W


System Power Watts 10.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32-36Vdc/250mA

Controls

Standard Switchable On/Off

Optional DDIM,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Wally	10W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Wally	10W	422	41	2700K	WW27K	CRI80		White	SWH	Non Dimmable	On/Off
		443	43	3000K	WW30K	CRI90		Black	SBL	Dali Dimmable	DDIM
		464	45	4000K	NW40K			Grey	GGT		
		474	46	5700K	CW57K						
Wally	10W			WW27K		CRI80			SWH	On/Off	