

## Ovo Mini TA | 5W

### Product Reference

Environment Indoor

Installation Track Mounted

### Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 3.4W


System Power Watts 4.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.5



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/350mA

### Controls

Standard Switchable On/Off

Optional Non Dimmable

### Ordering Details

| Code Example: | Name               | Watt      | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|--------------------|-----------|--------------|--------------|----------------|------------|---------------|
|               | <b>Ovo Mini TA</b> | <b>5W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>33°(MD)</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME        | WATT | LUMEN | EFFICACY | CCT   |       | CRI   | ANGLE   | FINISH |     | CONTROL      |        |
|-------------|------|-------|----------|-------|-------|-------|---------|--------|-----|--------------|--------|
| Ovo Mini TA | 5W   | 330   | 75       | 2700K | WW27K | CRI80 | 33°(MD) | White  | SWH | Non Dimmable | On/Off |
|             |      | 352   | 80       | 3000K | WW30K | CRI90 |         | Black  | SBL |              |        |
|             |      | 374   | 85       | 4000K | NW40K |       |         |        |     |              |        |
|             |      | 383   | 87       | 5700K | CW57K |       |         |        |     |              |        |
| Ovo Mini TA | 5W   |       |          | WW27K |       | CRI80 | 33°(MD) | SWH    |     | On/Off       |        |