
ABBY LIGHTING

50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3 | Swivel | Tilt

Optional: Bluetooth | Dimmable | Tunable White | Warm to Dim | CRI 90

Peeping Tom 48V | 10.8W





Product Reference

Environment Indoor

Installation Track Mounted

Construction & Materials

Housing Die Cast Aluminium,Milled Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 48V

Control Gear Included

Mounting Remote


LED Power Watts 10.6W

System Power Watts -

Operating Voltage Vin 48V

Power Factor p.f. -

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/300mA

Controls

Standard Switchable On/Off

Optional DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Peeping Tom 48V	**10.8W**	**WW27K**	**CRI80**	**28°(MD)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Peeping Tom 48V	**10.8W**	1018	96	2700K	**WW27K**	**CRI80**	28°(MD)	White	**SWH**	Non Dimmable	**On/Off**
		1049	99	3000K	**WW30K**	CRI90	36°(WD)	Black	**SBL**	Dali Dimmable	**DDIM**
		1102	104	4000K	**NW40K**		57°(VWD)			Bluetooth Dimmable	**BTTM**
		1124	106	5700K	**CW57K**					Casambi	**CBTM**
				2700K-5700K	**TW**						
				Warm to Dim	**W2D**						
Peeping Tom 48V	**10.8W**			**WW27K**		**CRI80**	**28°(MD)**	**SWH**		**On/Off**	