

## Twinline P OPD 60 | 20W

### Product Reference

Environment Indoor

Installation Ceiling Suspended

### Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 17.1W


System Power Watts 19.7W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95



Adjustable  
Suspension Kit



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/500mA

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                     | Watt       | CCT          | CRI          | Angle       | Finish     | Control       |
|---------------|--------------------------|------------|--------------|--------------|-------------|------------|---------------|
|               | <b>Twinline P OPD 60</b> | <b>20W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>110°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME              | WATT | LUMEN | EFFICACY | CCT         |       | CRI   | ANGLE | FINISH |     | CONTROL       |        |
|-------------------|------|-------|----------|-------------|-------|-------|-------|--------|-----|---------------|--------|
| Twinline P OPD 60 | 20W  | 1497  | 76       | 2700K       | WW27K | CRI80 | 110°  | White  | SWH | Non Dimmable  | On/Off |
|                   |      | 1537  | 78       | 3000K       | WW30K | CRI90 |       | Black  | SBL | Dali Dimmable | DDIM   |
|                   |      | 1615  | 82       | 4000K       | NW40K |       |       | Custom | CSM | Casambi       | CBTM   |
|                   |      | 1655  | 84       | 5700K       | CW57K |       |       |        |     |               |        |
|                   |      |       |          | 2700K-5700K |       |       |       | TW     |     |               |        |
| Twinline P OPD 60 | 20W  |       |          | WW27K       |       | CRI80 | 110°  | SWH    |     | On/Off        |        |

