

Roa Deep OPD 60 | 20W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish -

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 17.1W

System Power Watts 19.7W

Operating Voltage Vin 220-240Vac


Power Factor p.f. >0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Roa Deep OPD 60	20W	WW27K	CRI80	94°		On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Roa Deep OPD 60	20W	1596	81	2700K	WW27K	94°		Non Dimmable	On/Off	
		1656	84	3000K	WW30K			CRI90	Dali Dimmable	DDIM
		1734	88	4000K	NW40K				Casambi	CBTM
		1773	90	5700K	CW57K					
				2700K-5700K	TW					
Roa Deep OPD 60	20W			WW27K	CRI80	94°		On/Off		



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI