

Dark Knight S 3 | 16W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Aluminium Extrusion

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster - ABS

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 14.2W

System Power Watts 16.3W


Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95




Light Distribution


$\eta = 100\%$



$\eta = 100\%$



$\eta = 100\%$



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB 1304 3x9Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Dark Knight S 3	16W	WW27K	CRI80	20°(ss)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Dark Knight S 3	16W	1410	86	2700K	WW27K	CRI80	20°(ss) 26°(MD)	White SWH Non Dimmable On/Off
		1500	92	3000K	WW30K	CRI90	26°(MD)	Black SBL Phase Dimmable PDIM
		1590	98	4000K	NW40K		38°(WD)	Custom CSM Dali Dimmable DDIM
		1635	100	5700K	CW57K			
Dark Knight S 3	16W			WW27K	CRI80	20°(ss)	SWH	On/Off