

## Tiny TL | 10W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 8.7W


System Power Watts 10.0W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name           | Watt       | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|----------------|------------|--------------|--------------|----------------|------------|---------------|
|               | <b>Tiny TL</b> | <b>10W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>50°(MD)</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME    | WATT | LUMEN | EFFICACY | CCT         |       | CRI   | ANGLE   | FINISH |     | CONTROL            |        |
|---------|------|-------|----------|-------------|-------|-------|---------|--------|-----|--------------------|--------|
| Tiny TL | 10W  | 820   | 82       | 2700K       | WW27K | CRI80 | 50°(MD) | White  | SWH | Non Dimmable       | On/Off |
|         |      | 850   | 85       | 3000K       | WW30K | CRI90 | 61°(WD) | Black  | SBL | Phase Dimmable     | PDIM   |
|         |      | 890   | 89       | 4000K       | NW40K |       |         | Custom | CSM | Dali Dimmable      | DDIM   |
|         |      | 920   | 92       | 5700K       | CW57K |       |         |        |     | Bluetooth Dimmable | BTTM   |
|         |      |       |          | 2700K-5700K | TW    |       |         |        |     | Casambi            | CBTM   |
|         |      |       |          | Warm to Dim | W2D   |       |         |        |     |                    |        |
| Tiny TL | 10W  |       |          | WW27K       |       | CRI80 | 50°(MD) | SWH    |     | On/Off             |        |

