

Tiny Wash V2 | 5W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 3.6W


System Power Watts 4.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.5



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/130mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example: Name Watt CCT CRI Angle Finish Control

Tiny Wash V2 5W WW27K CRI80 SWH On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Tiny Wash V2	5W	392	87	2700K	WW27K	CRI80		White	SWH	Non Dimmable	On/Off
		405	90	3000K	WW30K	CRI90		Black	SBL	Phase Dimmable	PDIM
		423	94	4000K	NW40K			Custom	CSM	Dali Dimmable	DDIM
		432	96	5700K	CW57K					Casambi	CBTM
Tiny Wash V2	5W			WW27K		CRI80		SWH		On/Off	