

## Lensed Wallwasher | 20W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 16.2W


System Power Watts 20.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                     | Watt       | CCT          | CRI          | Angle | Finish     | Control       |
|---------------|--------------------------|------------|--------------|--------------|-------|------------|---------------|
|               | <b>Lensed Wallwasher</b> | <b>20W</b> | <b>WW27K</b> | <b>CRI80</b> |       | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME              | WATT | LUMEN | EFFICACY | CCT         |       | CRI   | ANGLE | FINISH |     | CONTROL            |        |
|-------------------|------|-------|----------|-------------|-------|-------|-------|--------|-----|--------------------|--------|
| Lensed Wallwasher | 20W  | 995   | 49       | 2700K       | WW27K | CRI80 |       | White  | SWH | Non Dimmable       | On/Off |
|                   |      | 1035  | 51       | 3000K       | WW30K | CRI90 |       | Black  | SBL | Phase Dimmable     | PDIM   |
|                   |      | 1096  | 54       | 4000K       | NW40K |       |       |        |     | Dali Dimmable      | DDIM   |
|                   |      | 1117  | 55       | 5700K       | CW57K |       |       |        |     | Bluetooth Dimmable | BTTM   |
|                   |      |       |          | Warm to Dim | W2D   |       |       |        |     | Casambi            | CBTM   |
| Lensed Wallwasher | 20W  |       |          | WW27K       |       | CRI80 |       | SWH    |     | On/Off             |        |

