

Outline Wallgrazer 120 | 20W

Product Reference

Environment Outdoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 16.9W


System Power Watts 19.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Outline Wallgrazer 120	20W	WW27K	CRI80	91°x 30°	AL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Outline Wallgrazer 120	20W	2134	110	2700K	WW27K	CRI80	91°x	91°x	Anodised	AL	Non Dimmable	On/Off
							30°	30°	Aluminium			
		2192	113	3000K	WW30K	CRI90					Phase Dimmable	PDIM
		2309	119	4000K	NW40K					Dali Dimmable	DDIM	
		2347	121	5700K	CW57K					Bluetooth	BTTM	
										Dimmable		
			2700K- 5700K	TW					Casambi	CBTM		

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Outline Wallgrazer 120	20W			WW27K	CRI80	91°x 30°	AL	On/Off