

# Outline Wallgrazer 120 | 40W

## Product Reference

Environment Outdoor

Installation Ceiling Surface

## Construction & Materials

Housing Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 34.1W


System Power Watts 39.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt;0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/1000mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name                   | Watt | CCT   | CRI   | Angle    | Finish | Control |
|---------------|------------------------|------|-------|-------|----------|--------|---------|
|               | Outline Wallgrazer 120 | 40W  | WW27K | CRI80 | 91°x 30° | AL     | On/Off  |

Select one from each column with highlighted values to create the ordering code

| NAME                   | WATT | LUMEN | EFFICACY | CCT         | CRI   | ANGLE    | FINISH                | CONTROL                 |
|------------------------|------|-------|----------|-------------|-------|----------|-----------------------|-------------------------|
| Outline Wallgrazer 120 | 40W  | 4077  | 104      | 2700K       | WW27K | 91°x 30° | Anodised Aluminium AL | Non Dimmable On/Off     |
|                        |      | 4194  | 107      | 3000K       | WW30K |          |                       | Phase Dimmable PDIM     |
|                        |      | 4390  | 112      | 4000K       | NW40K |          |                       | Dali Dimmable DDIM      |
|                        |      | 4469  | 114      | 5700K       | CW57K |          |                       | Bluetooth Dimmable BTTM |
|                        |      |       |          | 2700K-5700K | TW    |          |                       | Casambi CBTM            |
| Outline Wallgrazer 120 | 40W  |       |          | WW27K       | CRI80 | 91°x 30° | AL                    | On/Off                  |

