

## CoCo 35 | 22W

### Product Reference

Environment Indoor

Installation Ceiling Suspended

### Construction & Materials

Housing Spun Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 18.4W


System Power Watts 21.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 30V-38Vdc/500mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name           | Watt       | CCT          | CRI          | Angle       | Finish     | Control       |
|---------------|----------------|------------|--------------|--------------|-------------|------------|---------------|
|               | <b>CoCo 35</b> | <b>22W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>100°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME           | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE       | FINISH     | CONTROL        |
|----------------|------------|-------|----------|--------------|--------------|-------------|------------|----------------|
| <b>CoCo 35</b> | <b>22W</b> | 1118  | 53       | 2700K        | <b>WW27K</b> | 100°        | White      | Non Dimmable   |
|                |            | 1161  | 55       | 3000K        | <b>WW30K</b> |             | Black      | Phase Dimmable |
|                |            | 1224  | 58       | 4000K        | <b>NW40K</b> |             | Custom     | Dali Dimmable  |
|                |            | 1266  | 60       | 5700K        | <b>CW57K</b> |             |            | Casambi        |
| <b>CoCo 35</b> | <b>22W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> | <b>100°</b> | <b>SWH</b> | <b>On/Off</b>  |