

# Invictus 60 | 28W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Spun Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal, Microprismatic

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 22.7W


System Power Watts 26.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. &gt; 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 &gt;50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/700mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name               | Watt       | CCT          | CRI          | Angle       | Finish     | Control       |
|---------------|--------------------|------------|--------------|--------------|-------------|------------|---------------|
|               | <b>Invictus 60</b> | <b>28W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>110°</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME               | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE        | FINISH      | CONTROL                        |
|--------------------|------------|-------|----------|--------------|--------------|--------------|-------------|--------------------------------|
| <b>Invictus 60</b> | <b>28W</b> | 2767  | 106      | 2700K        | <b>WW27K</b> | <b>CRI80</b> | <b>110°</b> | Non Dimmable <b>On/Off</b>     |
|                    |            | 2845  | 109      | 3000K        | <b>WW30K</b> |              |             | Phase Dimmable <b>PDIM</b>     |
|                    |            | 2975  | 114      | 4000K        | <b>NW40K</b> |              |             | Dali Dimmable <b>DDIM</b>      |
|                    |            | 3054  | 117      | 5700K        | <b>CW57K</b> |              |             | Bluetooth Dimmable <b>BTDM</b> |
|                    |            |       |          | 2700K-5700K  | <b>TW</b>    |              |             | Casambi <b>CBTM</b>            |
| <b>Invictus 60</b> | <b>28W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> | <b>110°</b>  | <b>SWH</b>  | <b>On/Off</b>                  |