

Hoopla Dark 150 | 90W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster - PC

Body Finish White,Black,Custom

Diffuser PMMA Frosted

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 77.6W


System Power Watts 89.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Osram/Cree 3030 LED 33V-36Vdc/2250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Hoopla Dark 150	90W	WW27K	CRI80	45°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Hoopla Dark 150	90W	7671	86	2700K WW27K	CRI80	45°	White SWH	Non Dimmable On/Off
		7939	89	3000K WW30K	CRI90		Black SBL	Phase Dimmable PDIM
		8296	93	4000K NW40K			Custom CSM	Dali Dimmable DDIM
		8474	95	5700K CW57K				Bluetooth Dimmable BTTM
								Casambi CBTM
Hoopla Dark 150	90W			WW27K	CRI80	45°	SWH	On/Off