

Xo Pro 50 | 10W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 8.9W





System Power Watts 10.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTMM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Xo Pro 50	10W	WW27K	CRI80	21°(SS)	SWH	On/off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Xo Pro 50	10W	928	91	2700K	WW27K	CRI80	21°(SS)	White	SWH	Non Dimmable	On/Off
		959	94	3000K	WW30K	CRI90	30°(MD)	Black	SBL	Phase Dimmable	PDIM
		1010	99	4000K	NW40K		33°(WD)	Custom	CSM	Dali Dimmable	DDIM
		1030	101	5700K	CW57K		50°(VWD)			Bluetooth Dimmable	BTMM
				2700K-5700K Warm to Dim	TW W2D					Casambi	CBTM
Xo Pro 50	10W			WW27K		CRI80	21°(SS)	SWH		On/off	