

## Go Pro 35 TT | 9W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 7.5W




System Power Watts 8.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/200mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                | Watt      | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|---------------------|-----------|--------------|--------------|----------------|------------|---------------|
|               | <b>Go Pro 35 TT</b> | <b>9W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>24°(MD)</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                | WATT      | LUMEN | EFFICACY | CCT                        |                   | CRI          | ANGLE          | FINISH     |            | CONTROL            |               |
|---------------------|-----------|-------|----------|----------------------------|-------------------|--------------|----------------|------------|------------|--------------------|---------------|
| <b>Go Pro 35 TT</b> | <b>9W</b> | 697   | 81       | 2700K                      | <b>WW27K</b>      | <b>CRI80</b> | 24°(MD)        | White      | <b>SWH</b> | Non Dimmable       | <b>On/Off</b> |
|                     |           | 722   | 84       | 3000K                      | <b>WW30K</b>      | CRI90        | 36°(WD)        | Black      | <b>SBL</b> | Phase Dimmable     | <b>PDIM</b>   |
|                     |           | 757   | 88       | 4000K                      | <b>NW40K</b>      |              | 52°(VWD)       |            |            | Dali Dimmable      | <b>DDIM</b>   |
|                     |           | 783   | 91       | 5700K                      | <b>CW57K</b>      |              |                |            |            | Bluetooth Dimmable | <b>BTTM</b>   |
|                     |           |       |          | 2700K-5700K<br>Warm to Dim | <b>TW<br/>W2D</b> |              |                |            |            | Casambi            | <b>CBTM</b>   |
| <b>Go Pro 35 TT</b> | <b>9W</b> |       |          | <b>WW27K</b>               |                   | <b>CRI80</b> | <b>24°(MD)</b> | <b>SWH</b> |            | <b>On/Off</b>      |               |