

GrassHopper | 22W

Product Reference

Environment Outdoor
 Installation Ceiling Surface, Floor Surface, Wall Surface, Wall Surface

Construction & Materials

Housing Die Cast Aluminium
 Primary Lens PMMA
 Primary Reflector -
 Secondary Reflector -
 Body Finish Black, Grey
 Diffuser -
 Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
 Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable
 Tilt Yes
 Swivel No

Electrical System


Driven with Constant Current Driver
 Input Voltage/Hz 220V- 240V/50-60Hz
 Control Gear Included
 Mounting Integral
 LED Power Watts 18.1W
 System Power Watts 20.8W
 Operating Voltage Vin 220-240 Vac
 Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	GrassHopper	22W	WW27K	CRI90	16°(SS)	SBL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
GrassHopper	22W	1747	84	2700K	WW27K	CRI90	16°(SS)	Black SBL Non Dimmable On/Off
		1810	87	3000K	WW30K		25°(MD)	Grey GGT
		1893	91	4000K	NW40K		46°(WD)	
		1934	93	5700K	CW57K			
GrassHopper	22W			WW27K	CRI90	16°(SS)	SBL	On/Off



Light Distribution

LED Technology

Binning 3 Step MacAdam
 LED Life Time @ L80/B10 >50000 hours
 Colour Rendering (CRI) CRI90
 Led Type SMD high power
 LED Fitted Osram LED 22V-27Vdc/700mA

Controls

Standard Switchable On/Off
 Optional Non Dimmable